



---

# ARDEX P 9

## Single Part Primer

---

Improves adhesion to smooth, dense and non porous substrates

For internal and external walls and floors

Water-based - Solvent Free

Low VOC content - meets Green Building Council of Australia Green Star IEQ-13 requirements

---

**ARDEX Australia Pty Ltd**  
20 Powers Road  
Seven Hills NSW 2147  
Phone: 1300 788 780  
Fax: 1300 780 102  
Email: [technicalservices@ardexaustralia.com](mailto:technicalservices@ardexaustralia.com)  
[www.ardexaustralia.com](http://www.ardexaustralia.com)

**ARDEX New Zealand Ltd**  
32 Lane Street  
Woolston, Christchurch 8241  
Phone: 0800 227 339  
Fax: (03) 3849779  
Email: [info@ardexnz.com](mailto:info@ardexnz.com)  
[www.ardex.co.nz](http://www.ardex.co.nz)

# ARDEX P9

## Single Part Primer

### DESCRIPTION

ARDEX P9 Single Part Primer is a water-based primer used for improving the adhesion of ARDEX products to smooth, dense and various non porous substrates. It is easy to apply with a brush or roller with applications of subsequent products able to take place with minimal downtime.

ARDEX P9 Single Part Primer is suitable for internal and external wall or floor applications.

### FOR USE WITH

ARDEX P9 Single Part Primer is compatible with subsequent applications of ARDEX manufactured tile adhesives, floor levelling compounds and in non fully immersed conditions with ARDEX manufactured undertile waterproofing membranes.

### TO (SUBSTRATES)

Particleboard, plywood, sheet timber.  
Medium density fibre-cement sheet, compressed fibre-cement sheet.  
Jointing compound over plasterboard  
Concrete, renders, screeds  
Masonry and lightweight concrete blocks  
Autoclaved aerated concrete (AAC)  
Existing Glazed Tiles (not suitable for shower floors or permanently immersed conditions).  
Metal Surfaces  
Some plastics (contact Ardex on specific types)  
Epoxy Coatings (contact Ardex on specific coating)  
Painted Surfaces

Contact ARDEX if other substrates are encountered.

### SUBSTRATE PREPARATION

The surface to be primed must be clean, firm and free of dust, dirt, oil, grease, curing compounds, release agents and old surface coatings.

Ensure surfaces are dry prior to application, with no residue or permanent dampness.

Surfaces must be suitable for the application of the subsequent product being used.

### APPLICATION

Stir product before use.

Spread the material using a brush or long nap roller to cover at a rate of at least 6-10/m<sup>2</sup> per litre over the entire surface to be primed.

All tools should be cleaned with water immediately after use.

### DRYING TIME

Ensure the ARDEX Single Part Primer is fully dry prior to the application of subsequent products, allow approximately 60 minutes at 23°C and 50% relative humidity.

Type of substrate being primed, porosity and climatic conditions will affect drying times, allow longer for lower temperatures or high relative humidity.

### COVERAGE

One litre of ARDEX P9 Single Part Primer is sufficient for 6 - 10m<sup>2</sup>, therefore the approximate coverage on each of the following units is: 1L per 6 - 10m<sup>2</sup> coverage will vary depending on the porosity of the surface and method of application.

### PACKAGING

ARDEX P9 Single Part Primer is packed in plastic pails - net volume 1L and 4L

### SHELF LIFE

ARDEX Single Part Primer has a shelf life of not less than 12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

Store away from direct sunlight. Replace lid tightly after use.

### Pay attention to the following:

Do not empty excess primer back into the original packaging as this may cause contamination of the contents.

Do not use in negative hydrostatic pressure situations.

Do not apply below 5°C or above 35°C.

### SAFETY PRECAUTIONS

This product is considered non hazardous and non toxic in normal usage.

Avoid contact with skin and eyes; in case of contact with the eyes, rinse immediately with plenty of water and seek medical advice; wear suitable gloves and eye protection and keep the product out of the reach of children. If swallowed do not induce vomiting, give a glass of water and contact a doctor.

For further material safety data, consult the latest Material Safety Data Sheet.

### TECHNICAL DATA

**Appearance:** Grey Liquid

**Coverage:** Approx 6 - 10m<sup>2</sup>/litre

**Drying Time:** Approx 20 minutes  
(at 23°C and 50% relative humidity)

**Toll Free Technical Services:**  
**1800 224 070 (Australia)**  
**0800 227 339 (NZ)**

**ARDEX Australia Pty Ltd**  
20 Powers Road  
Seven Hills NSW 2147  
Phone: 1300 788 780  
Fax: 1300 780 102  
Email: [technicalservices@ardexaustralia.com](mailto:technicalservices@ardexaustralia.com)  
[www.ardexaustralia.com](http://www.ardexaustralia.com)

**ARDEX New Zealand Ltd**  
32 Lane Street  
Woolston, Christchurch 8241  
Phone: 0800 227 339  
Fax: (03) 3849779  
Email: [info@ardexnz.com](mailto:info@ardexnz.com)  
[www.ardex.co.nz](http://www.ardex.co.nz)

### DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them. © ARDEX Australia Pty Ltd 2011. All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.