



ARDEX TPO

QuickSeam Flashing

Used for flashing metal roof edging profiles

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX TPO QuickSeam Flashing

DESCRIPTION

ARDEX TPO QuickSeam Flashing is a non-reinforced thermoplastic polyolefin membrane laminated to a white cured seaming tape. ARDEX TPO QuickSeam Flashing is used for flashing metal roof edging profiles and other details as indicated in the specifications and details.

PREPARATION

ARDEX TPO surfaces and metal substrates must be prepared with TPO QuickPrime, using a QuickScrubber or QuickScrubber Plus tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

APPLICATION

Install the ARDEX TPO QuickSeam Flashing material in accordance with current ARDEX TPO specifications, details and workmanship requirements. Do not use the product for 3-dimensional details or details where the product will have to be stretched.

COVERAGE

In accordance with the length of the detail. Refer to the ARDEX specifications and details for specific information.

CHARACTERISTICS

Physical

- Excellent moisture resistance
- Excellent resistance to heat
- Excellent green tack

Technical

	Tape	TPO Flashing
Base	rubber polymer	TPO
Colour	white	White or gray
Solids	100 %	100 %
Specific weight	0.98	1.15
Thickness	0.89 mm	0.76 mm
Width	146 mm	140 mm

PACKAGING/STORAGE/SHELF LIFE

Packaging :	0.14 m x 30.5 m roll, 2 rolls per carton.
Storage:	store material in its original unopened packaging at temperatures between 15°C and 25°C away from sources of physical damage or chemical contamination. Do not store in direct sunlight or at temperatures above 25°C.
Shelf life:	6 to 9 months can be expected when stored at 15°C to 25°C in original unopened containers indoors. Shelf life will be shortened if exposed to elevated temperatures.

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program.

Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations.

The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

ARDEX Australia Pty Ltd

New South Wales	Ph (02) 9851 9100	Fax (02) 9838 7970
Queensland	Ph (07) 3817 6000	Fax (07) 3881 3188
Victoria/Tasmania	Ph (03) 9308 9255	Fax (03) 9308 9332
South Australia	Ph (08) 8268 2511	Fax (08) 8345 3207
Western Australia	Ph (08) 9256 8600	Fax (08) 9455 1227

ARDEX New Zealand Ltd

Auckland	Ph (09) 5800 005	Fax (09) 5799 963
Wellington	Ph (04) 5685 949	Fax (04) 5686 376
Christchurch	Ph (03) 3843 029	Fax (03) 3849 779

Technical Services Toll Free: 1800 224 070