



ARDEX WPM 270

(Sheltercoat Solvent Based Primer)

Excellent durability, low viscosity

Designed for external applications

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Ph: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Ph: (03) 373 6900
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX WPM 270

(Sheltercoat Solvent Based Primer)

DESCRIPTION

ARDEX WPM 270 (Sheltercoat Primer Solvent Based) is a clear primer designed to lock particles on the substrate to achieve maximum adhesion for subsequent coatings. It has excellent durability and is a low viscosity binder that seals absorbent substrates and consolidates dust. Designed principally for external applications, care should be taken when using internally to ensure adequate ventilation exists during application.

TYPICAL APPLICATIONS

- New and old concrete.
- Timber.
- Compressed fibreboards.
- Primer for acrylic coatings.

BASIC APPLICATION REQUIREMENTS

Substrate preparation

The surface to be coated should be dry, clean, sound and free from oil, grease and flaking paint. New concrete should be left a minimum of 28 days and new render a minimum of 7 days before application commences. All cracks or holes exceeding 2mm are to be repaired before application commences.

Application

Apply with brush, long nap roller or conventional spray at a coverage rate of 6m²/litre. Ensure that the coating is applied evenly at the recommended coverage rates. Allow a drying time of at least one hour.

LIMITATIONS

Do not apply ARDEX WPM 270 if the surface temperature is below 5°C or above 35°C.

Surfaces must be dry prior to application.

Primed surfaces should preferably be overcoated within the same day of application to avoid intercoat contamination.

COVERAGE

Approximately 6 m²/litre. Coverage rate may vary depending on the porosity of the surface.

PACKAGING

20L metal pails.

CLEAN UP

Clean all equipment with general purpose thinners immediately after use.

STORAGE

ARDEX WPM 270 must be stored above 5°C.

SHELF LIFE

One year in unopened containers stored at 20°C.

SAFETY PRECAUTIONS

ARDEX WPM 270 is hazardous and a dangerous goods. It is harmful by inhalation and in contact with skin. It may cause lung damage if swallowed. It is irritating to the eyes and skin. Keep out of reach of children. Keep container tightly closed and in a well ventilated place. Take off immediately all contaminated clothing. In case of contact with eyes, rinse with plenty of water and contact a doctor or Poisons Information Centre.

ADDITIONAL INFORMATION IS LISTED IN THE MATERIAL SAFETY DATA SHEET.

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program.

Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations.

The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

ARDEX Australia Pty Ltd

Technical Services Toll Free: 1800 224 070

New South Wales	Ph (02) 9851 9100	Fax (02) 9838 7970
Queensland	Ph (07) 3817 6000	Fax (07) 3881 3188
Victoria/Tasmania	Ph (03) 8339 3100	Fax (03) 9308 9332
South Australia	Ph (08) 8406 2500	Fax (08) 8345 3207
Western Australia	Ph (08) 9256 8600	Fax (08) 9455 1227

ARDEX New Zealand Ltd

Technical Services Toll Free: 0800 227 339

Auckland	Ph (09) 580 0005	Fax (09) 579 9963
Wellington	Ph (04) 568 5949	Fax (04) 568 6376
Christchurch	Ph (03) 373 6900	Fax (03) 384 9779