



ARDEX WPM 1000

Weldable Waterproofing Membrane

Versatile rubber waterproofing membrane

Heat weld laps and seams

Easy installation

Suitable for underground tanking, roofs, decks,
under-tiles, canal and pond linings

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 373 6900
Fax: (03) 384 9779
Internet: www.ardex.co.nz

ARDEX WPM 1000

Weldable Waterproofing Membrane

DESCRIPTION

ARDEX WPM 1000 Weldable Waterproofing Membrane is a versatile rubber membrane that can be heat welded. It is suitable for waterproofing underground tanking, rooftops, decks, undertile, canal and pond linings.

ARDEX WPM 1000 is made up of synthetic rubber with properties which resist ageing from heat, sunlight and ozone and is heat weldable. Polypropylene filaments are welded onto both sides of the membrane for better wetting by water based adhesives. It has excellent gas impermeability and toughness and remains flexible at low temperatures.

Laps and corners are to be heat formed and/or welded. Tiling can be done directly on the membrane after 60 minutes with common ARDEX tiling adhesives like X77, X56 STS8/E90, Quickbond/Abalastic, 2 part Optima or ABAFLEX.

MATERIAL SPECIFICATIONS

ARDEX requirements for long term warranty necessitate that the ARDEX WPM 1000 meets these typical technical requirements:

TEST	SPEC
Gauge – 1.0mm & 1.5mm	+0.15
Specific Gravity	1.26
Tensile Strength (MPa) Min	6.00
300% Modulus (MPa) Min	4.00
Elongation at Break (%) Min	300%
Tear Die (kN/m) Min	26.25
Hardness (° IRHD)	75 ± 5
Tensile Retained Min %	70
Elongation at Break	
Retained Min %	70
Water Vapour	
Transmission g/(day.m ²)	0.11
Ozone Resistance to	
ASTM D1149 - 7 days	
at 40°C in 50pphm ozone	No visible cracks

GAUGES

Standard 1.0mm

RESISTANCE

ARDEX WPM 1000 resists tearing, flex cracking, bubbling and abrasion. It is extremely strong, has a long life and is versatile.

PACKAGING

In rolls of nominal 1.4m width and 20m long. Each roll is packed in polythene wrapper trademarked ARDEX WPM 1000.

ADHESIVES FOR USE WITH ARDEX WPM 1000

ARDEX WPM 09A - The standard contact brushing, spray grade and rolling solvent free adhesive for fixing to the substrate. Supplied

in 20L plastic containers.

ARDEX WPM 09C - Catalyst to assist adhesion in adverse conditions.

ARDEX WA98 - Solvent Based waterproofing adhesive.

ARDEX WPM 642 - Water Based Adhesive

DURABILITY

ARDEX WPM 1000 when fixed according to ARDEX instruction will meet the NZBC requirements of B2.3.1(b) 15 years.

SUBSTRATE SPECIFICATION

Plywood & Timber

Substrates must be dry when ARDEX WPM 1000 is applied. The plywood and timber substructure shall have a maximum moisture content of 20% when ARDEX WPM 1000 is adhered.

NOTE: LOSP (Light Organic Solvent Preservative) treated plywood must NOT be used under ARDEX WPM 1000 in any circumstances or conditions.

New Concrete

Must be cured for a minimum of 28 days and all curing compounds removed prior to application. A reduction in cure time can be achieved by utilising the ARDEX HydrEpoxy System (consult ARDEX Technical Department for details).

Old Concrete

Must be clean from any contaminants prior to application

OTHER SUBSTRATE TYPES

Fibre cement compressed sheet, closed cell polyurethane foam, wet wall linings i.e. Gib Aqualine, VillaBoard.

INSTALLATION

Roll out ARDEX WPM 1000 and cut to the measured length. Smooth ARDEX WPM 1000 on contact to minimise air entrapment beneath the membrane.

Floor sheets of ARDEX WPM 1000 must extend up the wall at least 150mm. Make sure the ARDEX WPM 1000 is laid tightly into all corners. Wall sheets of ARDEX WPM 1000 should overlap the 150mm upstand. Weld seams and laps with the Leister Triac S Hot Air Gun. Roll with a rubber roller to ensure seams and laps are secure.

Walls, internal corners & transitions

Apply the ARDEX WPM 1000 membrane 1800mm up the walls or to a height of 150mm above the shower rose. For unenclosed showers the membrane must extend a minimum of 1500mm out from the shower rose.

PROTECTION

ARDEX WPM 1000 is not suitable as a trafficable surface. ARDEX WPM 1000 is compatible with undertile heating systems. For electric undertile heating, the wire must be covered with a thin screed prior to laying the membrane.

It is the responsibility of the main building contractor to ensure all sub-trades likely to be working in the vicinity of the membrane are aware that a waterproofing membrane has been installed and all care must be taken to protect the membrane from damage. The tiler must lay tiles in accordance with best practice guidelines.

ARDEX Australia Pty Ltd

Technical Services Toll Free: 1800 224 070

NSW	Ph (02) 9851 9100	Fax (02) 9838 7970
QLD	Ph (07) 3817 6000	Fax (07) 3881 3188
VIC/TAS	Ph (03) 9308 9255	Fax (03) 9308 9332
SA	Ph (08) 8268 2511	Fax (08) 8345 3207
WA	Ph (08) 9256 8600	Fax (08) 9455 1227

ARDEX New Zealand Ltd

Technical Services Toll Free: 0800 227 339

Auckland	Ph (09) 580 0005	Fax (09) 2967 689
Wellington	Ph (04) 5685 949	Fax (04) 5686 376
Christchurch	Ph (03) 373 6900	Fax (03) 3849 779

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable New Zealand & Australian Standards, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them. All aforementioned products are the trade marks of ARDEX New Zealand Ltd.