

## **CONTENTS**

nis is ARDEX	5	ARDEX WA 98 S	34
novation	6	ARDEX WPM 710 DT	34
ystem ARDEX	7		
arranties	9	BUTYNOL ROOFING	
raining	10		
ustainability	11	ARDEX BUTYNOL®	37
upport	12	ARDEX WA 98	37
		ARDEX WPM 295	38
RODUCT SYSTEMS		ARDEX WPM 299	38
		ARDEX DETAIL TAPE	39
at Roofing - Residental and Commercial	14	ARDEX SEAM TAPE	39
at Roofing - Heat-Sensitive Substrate option	15	ARDEX FLASHING TAPE	40
at Roofing - Torch Applied Concrete Substrate	16		
at Roofing - Industrial Mechanically Fastened	17	TPO ROOFING	
at Roofing - Industrial Fully Adhered	18		
at Roofing - Remedial	19	ULTRAPLY TPO 1.14MM	43
at Roofing - Warm Roof	20	ULTRAPLY TPO 1.5MM	43
at Roofing - Green Roof	21	TPO BONDING ADHESIVE	44
at Roofing - Guttering	22	ARDEX TPO MEMBRANE DETAILING	44
xternal Tiling - Tiled Deck	23	ARDEX FASTENERS	45
eck System - Timber Deck	24	ARDEX HD SEAM PLATES	45
elow Grade System - Damp Proofing	25	TPO UNREINFORCED FLASHING	46
elow Grade System - Torch Applied	26	ARDEX QUICKSEAM FLASHING	46
elow Grade System - Tanking	27		
ternal Tiling - Liquid Membrane	28	TORCH-APPLIED ROOFING	
ternal Tiling - WeldTec™ Sheet Membrane	29	TORCH-APPLIED ROOFING	
ternal Vinyl Floor Covering	30	ARDEX WPM 114	49
EL DIE ON DOCEMIO		ARDEX WPM 117	49
ELDTEC™ ROOFING		ARDEX WPM 120	50
		ARDEX WPM 180	50
RDEX WPM 715	33	ARDEX WPM 189	51
RDEX WA 98 A	33	ARDEX WPM 189+	51
RDEX WA 98 A	33		

ARDEX WPM 240	52
ARDEX WPM 247	52
ARDEX BITUMINOUS SEALANT	53
DAMP-PROOF MEMBRANES	
ARDEX WPM 3000X	55
ARDEX WPM 5000HD	55
ARDEX DRS 10 GC	56
ARDEX BITUMINOUS SEALANT	56
ARDEX WPM 240	57
ARDEX WPM 247	57
BELOW GRADE AND TANKING MEMBRANES	
ARDEX WPM 179	59
ARDEX WPM 195	59
ARDEX WPM 196	60
ARDEX WPM 1000 RR	60
ARDEX WPM 1500	61
ARDEX DRS 10 GC	61
ARDEX WPM 1955	62
WELDTEC™ UNDERTILE MEMBRANES	
ARDEX WPM 750	65
ARDEX WPM 1000	65
ARDEX WA 98	66
ARDEX WeldTec™ DETAILING	66
ARDEX UD 150	67
ARDEX UP 158	67

LIQUID MEMBRANES	
ARDEX WPM 001	69
ARDEX WPM 002	69
ARDEX WPM 155 RAPID	70
ARDEX WPM 300	70
ARDEX DECKWEB	71
ARDEX ST TAPE	71
ARDEX MULTIPRIME	72
ARDEX P 9	72
THERMAL INSULATION BOARDS	
ARDEX POLYISO INSULATION BOARD	75
ARDEX HD COVER BOARD	75
ARDEX INSULATION PLATES	76
ARDEX FASTENERS	76
DRAINAGE SYSTEMS	
ARDEX UD 150	79
ARDEX DRS 10 GC	79
ARDEX UD 158	80
DISCLAIMER	83

P2 | ARDEX Group ardex.co.nz | P3

ARDEX HAS A HISTORY OF BREAKTHROUGH INNOVATIONS, WHICH HAVE CHANGED THE INDUSTRY.

## THIS IS ARDEX

For more than 70 years, ARDEX has been the quality leader for an entire industry. ARDEX specialises in high quality construction materials for substrate preparation, floor levelling, waterproofing and the fixing and grouting of surface materials.

When it comes to floor levelling and adhesives, waterproofing membranes and decorative finishes. ARDEX is the brand of choice for installers and wholesalers.

> ARDEX is an independent family-owned business, which means that, in our permanent efforts to achieve market-shaping innovations, we are able to retain our most important tradition: uncompromising quality.

> Strong internal growth and intelligent acquisitions in foreign markets have put the ARDEX Group on the map with 71 subsidiaries, and over 3,900 employees in over 50 countries. It's no coincidence ARDEX is regarded as the premium partner in the building materials sector.





## **INNOVATION**

Since it was founded in 1949, ARDEX has been known all over the globe as an innovative leader for specialist building products. As the inventors of self-levelling and smoothing compounds, ARDEX has a history of breakthrough innovations, that have driven and changed the market.

ARDEX products including Arditex, X 77, FG 8 Grout and WeldTec™ are firmly established as benchmarks for use worldwide.

The heart of ARDEX product development is the central laboratory in Witten, Germany. This lab partners with centres of excellence around the world to ensure the consistent quality of the products and maximum responsiveness to local market needs.

Innovation at ARDEX is not confined to research and development. It is an organic system comprising of cutting-edge customer insight research, close cooperation with associations and universities, and strong interaction between sales, marketing, technical services and purchasing.

# SYSTEM ARDEX

ARDEX is committed to developing products that are easy to use and offer high performance. Each product is the careful result of research and development combined with the input of contractors and installers to ensure absolute product compatibility.

Our systematic global Stage Gate Process for the introduction of new products is designed to optimise speed to market as well as to ensure superior quality and reliability for our customers. On-site product testing is an integral part of that process.


ARDEX products, systems and services are designed to ensure professional contractors have the competitive advantage of a lower total cost of installation through superior performance.



As a longstanding partner to trade, we know the practical requirements first-hand. Our vast experience with materials and working methods and our constant dialogue with customers in skilled trades are our most important source of inspiration. We draw on this to develop product systems that command respect in the market place. Our systems are optimally matched and extremely cost-effective thanks to their ease and speed of processing and high coverage.



P6 ARDEX Group ardex.co.nz P7



## **WARRANTIES**

The major point of difference between a SystemARDEX™ warranty and other warranties is the extent of cover provided for the owner or builder. Most competitor product warranties cover only the replacement of the defective product. That is further reduced through a discounting structure based on years of service prior to the claim. And usually, no cover is provided for the costs incurred in removing the defective product and installing the replacement product.



A SystemARDEX warranty covers:

- The costs of repair to which the product is applied and damaged by removal of the defective product where such proves necessary.
- The cost of reinstating or repairing the product or system including material costs of equal or equivalent products.
- The costs of rectifying any material covering the product.

SystemARDEX™ warranty claims are NOT discounted by years of service of defective products or any damage to the surface or material.

The SystemARDEX™ Warranty is project specific and warrants that the SystemARDEX<sup>™</sup> combination of products that forms the total system are free from defects, are 100% compatible and the system combination is suitable for the purpose intended.



## **TRAINING**

Our industry, like any other, requires ongoing training to keep up with changes in legislation, standards and materials. ARDEX offers training for both the applicator as well as staff.

For members of the construction industry committed to providing a high level of workmanship, ARDEX can help stay up to date, and increase both knowledge and confidence

Training courses offered by ARDEX:

- · CPD seminars for specifiers
- ARDEX undertile liquid waterproofing training
- ARDEX floor levelling training
- ARDEX WeldTec<sup>™</sup> Membrane training
- ARDEX external waterproofing training Butynol, TPO and Torch On
- ARDEX retail training

In order to encourage information exchange and creativity across borders, ARDEX strongly supports international career paths. We realise that we need the most talented people to maintain and extend our innovation leadership.

## **SUSTAINABILITY**

Sustainability is a business principle at ARDEX where we focus on creating products of premium quality and functional performance, coupled with exceptional reliability and durability. In addition, sustainability is one of the cornerstones of our corporate philosophy. We demonstrate our commitment to the pillars of sustainability – environment, economic and social, in both our daily work, as well as our long-term goals.



Long before it became a buzzword, the concept of sustainability was already an integral part of the ARDEX corporate philosophy.

- High-coverage ARDEX products takes care of large surface areas with minimal material, cutting down on processing, transport and waste packaging.
- Reduce back-and-forth travel to the building site with ARDEX products providing fast, easy installation.
- ARDEX products are engineered for a long life, meaning less wastage and more saved resources.
- ARDEX's remedial and repair products are great for refurbishments - eliminating the need for a demolition and new build using up more resources.
- High-quality ARDEX sub-floor smoothing compounds create extremely even surfaces, meaning far less adhesive is required to affix the flooring.

P10 | ARDEX Group ardex.co.nz | P11

## **SUPPORT SERVICES**

The ARDEX support team is dedicated to eliminating guesswork, improving on site efficiencies and taking the risk out of product and system installation.

For information on products, field support, customer service, training products or product demonstrations please contact us:

#### 0800 227 339

#### ardex.co.nz

Also visit our Facebook and Youtube pages for product news and updates, introduction to new products and access to our extensive video library.

www.facebook.com/ARDEXNZ

www.youtube.com/ardexaustralia


@ardexnewzealand




The ARDEX website is optimised for mobile devices and features an easy-to-use product calculator tool, as well as other helpful tools available in the palm of your hand. Scan the QR code below to access the ARDEX website on your mobile phone.







Residential and Commercial option





#### ARDEX WPM 715

WeldTec™ 1.5mm weldable waterproofing membrane



#### ARDEX WA 98

Waterproofing membrane adhesive

#### Selected substrate


- Concrete
- Timber
- Modified bitumen
- ARDEX Polyiso or HD Cover Board
- CFC sheet
- Galvanised metal
- Zincalume
- Polyurethane foam

#### ARCHITECTS, SPECIFIERS AND DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

## **FLAT ROOFING SYSTEM 2**

Torch Applied - Heat-Sensitive Substrate option





#### ARDEX WPM 189+

Ceramic-coated top layer bitumen membrane

## **ARDEX WPM 117**

### Self-adhesive,

fibre-reinforced bituminous membrane



#### ARDEX **WPM 240**

Solvent-based bitumen primer

#### **ARDEX** WPM 247

Water-based bitumen primer



For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

#### Selected substrate

- Timber
- ARDEX Polyiso Board

P14 | ARDEX Group ardex.co.nz P15

Torch Applied - Concrete Substrate option





#### ARDEX WPM 189+ Ceramic-coated top layer bitumen membrane

ARDEX WPM 114

Vented base sheet for moisture issues


Concrete substrate

#### ARCHITECTS, SPECIFIERS AND DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

## **FLAT ROOFING SYSTEM 4**

Industrial - Mechanically Fastened option



#### ARDEX **Heavy Duty Fasteners**

TPO and linsulation fastening

**Optional ARDEX** 

bituminous membrane

WPM 3000X

Self-adhesive

#### **ARDEX** Insulation Plates

OR

ARDEX

membrane

WPM 5000 HD

Industrial-strength,

self-adhesive bituminous

For fastening of ARDEX Polyiso Board

#### **ARDEX** Polyiso Board

OR

PIR foam insulation board

#### ARDEX HD Cover Board

High-density Polyiso Cover Board

#### ARCHITECTS, SPECIFIERS AND DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

Suitable substrate

P16 | ARDEX Group ardex.co.nz P17

#### Industrial - Fully Adhered option



### FIRESTONE ULTAPLY TPO 1.14mm

1.14mm TPO large-scale roofing membrane

OR




### FIRESTONE ULTRAPLY TPO 1.5mm

1.5mm TPO large-scale roofing membrane

2

#### ARDEX WPM 649

TPO bonding adhesive



3

### ARDEX OR Polyiso Board

PIR foam insulation board fixed down with Polyiso adhesive or fasteners

#### ARDEX HD Cover Board

High-density Polyiso Cover Board

4

### Optional ARDEX WPM 3000X

Self-adhesive bituminous membrane

#### OR ARDEX WPM 5000 HD

Industrial-strength, self-adhesive bituminous membrane

5


Suitable substrate

#### ARCHITECTS, SPECIFIERS AND DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

## **FLAT ROOFING SYSTEM 6**

Remedial option





#### ARDEX BUTYSEAL

WeldTec<sup>™</sup> fleece-lined waterproofing membrane

#### ARDEX WA 98

Waterproofing membrane adhesive

3


Imperfect substrate or existing membrane

#### ARCHITECTS, SPECIFIERS AND DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

P18 | ARDEX Group ardex.co.nz | P19

Warm Roof option



**ARDEX WPM 715** WeldTec™ 1.5mm

weldable waterproofing membrane



ARDEX WA 98

Waterproofing membrane adhesive



#### **Optional ARDEX HD Cover Board**

High-density Polyiso Cover Board fixed down with Polviso adhesive or fasteners



#### ARDEX Polyiso Board

PIR foam insulation board fixed down with Polyiso adhesive or fasteners

Suitable substrate




#### Optional ARDEX WPM 3000X

Self-adhesive bituminous membrane

#### ARCHITECTS, SPECIFIERS AND DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

## **FLAT ROOFING SYSTEM 8**







Self-adhesive bituminous membrane


Substrate engineered to suit green roof

ARCHITECTS, SPECIFIERS AND DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

P20 | ARDEX Group ardex.co.nz P21

Guttering





#### ARDEX WPM 715

WeldTec™ 1.5mm weldable waterproofing membrane




ARDEX WA 98

Waterproofing membrane adhesive

ARCHITECTS,
SPECIFIERS AND
Selected substrate
DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

## **EXTERNAL TILING SYSTEM 1**



P22 | ARDEX Group ardex.co.nz | P23

Undertile drainage mat

WeldTec™ external undertile waterproofing membrane.

## **DECK SYSTEM 1**

Timber Deck

Timber decking

Timber bearer




DekCradle™

Timber decking support



ARDEX WA 98 A

Waterproofing membrane adhesive




WeldTec<sup>™</sup> weldable waterproofing membranes

Concrete substrate

ARCHITECTS, SPECIFIERS AND DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

## **BELOW GRADE SYSTEM 1**



ARDEX WPM 240 Solvent-based bitumen **ARDEX WPM 247** 

Water-based bitumen primer

Concrete substrate


primer

DESIGNERS

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

P24 | ARDEX Group ardex.co.nz P25

## **BELOW GRADE SYSTEM 2**




Concrete substrate

to your local ARDEX representative or visit ardex.co.nz

## **BELOW GRADE SYSTEM 3**

Pre-applied Tanking



Sacrificial formwork or shotcrete



ARDEX WPM 1500 WeldTec Below-Grade Tanking Membrane


Cast concrete

ARCHITECTS, SPECIFIERS AND **DESIGNERS** 

For specification support and project assistance, please contact ARDEX on 0800 227 339, speak to your local ARDEX representative or visit ardex.co.nz

P26 | ARDEX Group ardex.co.nz P27

## **INTERNAL TILING SYSTEM 1**





#### **ARDEX Multiprime**

Water-based primer


#### Selected substrate

Concrete, renders and screeds, fibre cement board, plywood

to your local ARDEX representative or visit ardex.co.nz

## **INTERNAL TILING SYSTEM 2**

WeldTec<sup>™</sup> Sheet Membrane option




#### Selected substrate

Concrete, renders and screeds, fibre cement board, plywood

to your local ARDEX representative or visit ardex.co.nz

P28 | ARDEX Group ardex.co.nz P29



Multiprime

Water-based primer

Water-based epoxy membrane for controlling hydrostatic pressure



K 900 BF

Bulk-fill levelling compound


OR ARDEX A 38

> Rapid-setting screed cement

For specification support and project assistance, please contact ARDEX on 0800 2 ARDEX, speak to your local ARDEX representative or visit www.ardex.co.nz



Concrete, renders and screeds, fibre cement board, plywood















ARDEX WPM 715 is a 1.5mm weldable waterproofing membrane with properties which resist ageing from heat, sunlight and ozone.

- Welded laps and seams for fast installation
- Excellent resistance to atmospheric agents

#### Typical use

- External
- Horizontal or vertical
- Decks and roofs

#### Substrates

- Concrete
- Plywood
- · Modified bitumen
- Malthoid
- ARDEX Polyiso or HD Cover Board
- Orientated strandboard
- CFC sheet
- Timber
- Galvanised metal
- Zincalume
- · Polyurethane foam

Gauge	1.5mm
Dimensions	20m x 1.4m (28m²)
Codes	Black and Grey: 32341

ARDEX WA 98 A is a high-performance roofing contact adhesive.

- Contact adhesive
- Solvent-based
- Ideal for bonding large areas

#### Typical use

- External
- · Horizontal or vertical
- Adhering ARDEX WeldTec<sup>™</sup> and Butynol sheet membranes

#### Suitable membrane types

- WeldTec<sup>™</sup>
- Butynol

Working time	15 – 60 minutes
Coverage	4 – 8m² bond area per litre
Codes	20L: 13052 4L: 10870 1L: 10869

## **ARDEX WPM 98 S**

**ARDEX WA 98 SOLVENT** 



Formerly known as ARDEX WPM 290. ARDEX WA 98 S is a mild solvent suitable for cleaning down surfaces and waterproofing membranes contaminated with dried ARDEX WA 98.

- Coagulates for easier removal
- Reduced damage to surfaces

#### Typical use

- Cleaning surfaces prior to adhesion
- Thinning ARDEX WA 98 when needed
- Re-activating dry adhesive surfaces
- Cleaning brushes and rollers
- Removing excess adhesive

Codes

20L: 13050 4L: 10874 1L: 10873 0.5L: 10872 0.25L: 10871

## **ARDEX WPM 710 DT**

WELDTEC™ EXTERNAL DETAIL TAPE




ARDEX WPM 710 DT is a weldable detail tape for use with external ARDEX WeldTec membranes.

- Available as tapes or patches
- Weldable
- Resistant to atmospheric agents

#### Typical use

- External
- Horizontal and vertical applications
- Detailing ARDEX WeldTec Membranes

Colours	Black, Dove Grey
Widths	Black 150mm patch: 32461 Black 300mm: 32443 Dove Grey 100mm: 32545 Dove Grey 150mm patch: 32462 Dove Grey 200mm: 37304 Dove Grey 300mm: 32444
Gauge	1mm
Tape length	20m











WATERPROOFING MEMBRANE ADHESIVE



ARDEX Butynol® is a synthetic rubber membrane with properties which resist ageing from heat, sunlight and ozone.

- Single-ply
- Flexible rubber synthetic membrane
- Remains flexible at low temperatures

#### Typical use

- External
- Horizontal or vertical applications
- · Decks, roofs, gutters

#### Substrates

- Concrete
- Plywood
- ARDEX Polyiso or HD Cover Board
- · Orientated strandboard
- CFC sheet
- Timber
- Galvanised metal
- Zincalume

Colours	Various
Gauge	Available in numerous thicknesses
Standard Dimensions*	17.86m x 1.4m (25m²)
	*Dimensions are customisable

ARDEX WA 98 A is a high-performance roofing contact adhesive.

- Contact adhesive
- Solvent-based
- Ideal for bonding large areas

#### Typical use

- External
- Horizontal or vertical
- Adhering ARDEX WeldTec<sup>™</sup> and Butynol sheet membranes

#### Suitable membrane types

- WeldTec<sup>™</sup>
- Butynol

Working time	15 – 60 minutes
Coverage	4 – 8m² bond area per litre
Codes	20L: 13052 4L: 10870

1L: 10869

## ARDEX WPM 98 S

**ARDEX WA 98 SOLVENT** 



## ARDEX WPM 299



**SEAM PRIMER** 

Formerly known as ARDEX WPM 290. ARDEX WA 98 S is a mild solvent suitable for cleaning down surfaces and waterproofing membranes contaminated with dried ARDEX WA 98 S.

- · Coagulates for easier removal
- Reduced damage to surfaces

#### Typical use

- Cleaning surfaces prior to adhesion
- Thinning ARDEX WA 98 S when needed
- Re-activating dry adhesive surfaces
- Cleaning brushes and rollers
- Removing excess adhesive

Codes

20L: 13050 4L: 10874 1L: 10873 0.5L: 10872 0.25L: 10871 ARDEX WPM 299 is primer-adhesive used with various ARDEX systems.

- Water resistant
- Improves seam tape adhesion
- Fast drying

#### Typical use

- External
- Bonding primer for ARDEX products

**Codes** 4L: 10205



ARDEX Detail Tape is a self-adhesive, butyl-based tape, self-protected by a polypropylene fleece.

- Excellent adhesion at low temperatures
- · Excellent heat stability
- High workability

#### Typical use

- Horizontal or vertical applications
- · Decks, roofs, gutters
- Below-grade applications

#### Substrates

- Galvanised metal
- Zincalume
- ARDEX Waterproofing membranes\*

Dimensions	30.4m x 150mm
Code	10584

## ARDEX SEAM TAPE

**SEAM TAPE FOR GENERAL LAP BONDING** 

ARDEX Seam Tape is a pressure-sensitive adhesive tape for bonding laps and seams of ARDEX Butynol membranes.

- Provides strong, watertight seams
- · Fast and easy installation
- · High tack

#### Substrates

• ARDEX Waterproofing membranes and outlets\*

Dimensions	30.4m x 50mm
Code	10539

\*Contact ARDEX for other applications

P38 ARDEX Group ardex.co.nz P39

# ARDEX FLASHING TAPE




A malleable tape for moulding in gussets, pipe flashings and awkward situations. Supplied in 100mm x 5m rolls. Flashing tape must not be left exposed. A cover strip of membrane or detail tape must be applied over flashing tape to finish.

Flashing tape can be welded to when used with the WeldTec® range.

ARDEX WA 98 must be used to adhere to the substrate and when used with the Butynol® system.

Dimensions	100mm x 5m roll
Code	10397





## **ULTRAPLY TPO 1.14MM**

**TPO ROOFING MEMBRANE 1.14MM** 



## ULTRAPLY **TPO 1.5MM**

**TPO ROOFING MEMBRANE 1.5MM** 



Ultraply TPO roof membrane is a high-performance waterproofing membrane, that is environmentally friendly, fast to install and safe to use. The benefits of TPO membranes range from heat reflectivity and energy efficiency to green roofing systems.

Previously known as ARDEX WPM 612.

- Energy efficient
- Fast to install
- No toxic emissions

#### Typical use

- External
- Roofing
- Low-slope
- Large roof areas

Gauge	1.14mm
Dimensions	30.5m x 3.05m (93m²)
Colour	Grey
Code	25225

Ultraply TPO roof membrane is a high-performance waterproofing membrane, that is environmentally friendly, fast to install and safe to use. The benefits of TPO membranes range from heat reflectivity and energy efficiency to green roofing systems.

Previously known as ARDEX WPM 615.

- Energy efficient
- Fast to install
- No toxic emissions

#### Typical use

- External
- Roofing
- Low-slope
- Large roof areas

Gauge	1.5mm
Dimensions	30.5m x 3.05m (93m <sup>2</sup> )
Colour	Grey
Code	13506

### TPO BONDING ADHESIVE



ARDEX TPO MEMBRANE DETAILING



Ultraply TPO Bonding Adhesive is a solvent based contact adhesive designed specifically for bonding Ultraply TPO membranes to approved insulations in addition to wood, metal, masonry and other acceptable substrates. Previously known as ARDEX 649.

Coverage	$1.40\text{m2}$ to $1.47\text{m}^2$ per litre may be obtained depending on the substrate
Substrates	Wood     Masonry     Metal     Others – check with your local ARDEX representative
Packaging	18.9L
Code	22082

ARDEX provide a range of pre-cut and moulded TPO flashing and detailing products.

- Pipe boots and flashings
- Corners
- Pockets

## Dimensions Refer to ardex.co.nz for dimensions, quantities and colours of each product

## ARDEX FASTENERS

TPO AND INSULATION FASTENING

ARDEX Fasteners are Heavy Duty Fasteners that are specifically designed for mechanical attachment of ARDEX TPO membranes and roofing insulation.

• 500 or 1000 pcs, dependent on screw length

#### Typical use

- External roofing
- With ARDEX thermal insulation systems
- Mechanically fastened systems

#### Thread size

Heavy Duty: 6.7mm

#### **Screw Length**

• From 32mm to 356mm

### ARDEX HD SEAM PLATES

**TPO SEAM PLATES** 

ARDEX HD Seam Plates are designed for attaching ARDEX TPO membranes to approved substrates in conjunction with ARDEX Heavy Duty Fasteners.

- Galvalume® Sheet steel material
- 4 inner and 4 outer eyehook extensions for holding power
- Corrosion resistance

Dimensions	Diameter circle: 60.3mm
	Gauge: 0.94mm
	Hole diameter: 6.7mm
Code	Pack of 1000: 12609

P44 ARDEX Group ardex.co.nz P45

## **TPO UNREINFORCED FLASHING**

TPO Unsupported Flashing is a non-reinforced Thermoplastic PolyOlefin Membrane designed to be used in roofing applications where ARDEX pre-moulded TPO accessory products are not appropriate. Previously known at ARDEX WPM 623.

Tear Resistance	≥400 N
Packaging	0.61m x 15.25m roll
Code	11052

## **ARDEX** QUICKSEAM FLASHING


**TPO FLASHING MEMBRANE** 

ARDEX TPO QuickSeam Flashing is a non-reinforced Thermoplastic Polyolefin membrane laminated to a white cured seaming tape.

- For flashing metal roof edge profiles
- Excellent moisture resistance
- Resistant to heat

Colours	Tape: White Flashing: White or Grey
Gauge	Tape: 0.89mm Flashing: 0.76mm
Dimensions	30.5m x 146mm
Code	Grey: 12956







**VENTED BASE SHEET FOR MOISTURE ISSUES** 



**ARDEX WPM 117** 

**SELF-ADHESIVE**, FIBRE-REINFORCED **BITUMINOUS MEMBRANE** 

ARDEX WPM 117 is a self-adhesive SBS modified bitumen membrane providing absolute waterproofing and resistance to hydrostatic pressure.

- · Reinforced with fibreglass
- Peel and stick installation

#### Typical use

- General waterproofing
- Base layer over heat sensitive substrates
- Areas where fire and torching must be avoided

#### Substrates

- Timber
- Zincalume®
- Aluminium
- Concrete
- ARDEX Polyiso Board

Gauge 2mm

Dimensions 15m x 1m (15m<sup>2</sup>)

Code 24560

where there may be substrate moisture issues. • Suitable for substrates with moisture issues

ARDEX WPM 114 is an APP modified bitumen membrane vented base sheet, for use in applications

· Excellent cold flexibility

#### Typical use

- External
- Roofing
- Base sheet in multi-layer systems

#### Substrates

Concrete screeds

Gauge 4mm

8m x 1m (8m<sup>2</sup>) **Dimensions** 

Code 32358

## ARDEX WPM 120

BASE/MID-LAYER
BITUMINOUS MEMBRANE



## ARDEX WPM 180

MULTI-LAYER REINFORCED BITUMINOUS MEMBRANE



ARDEX WPM 120 is an APP modified bitumen membrane, with a sanded or talc top finish and a heat-sensitive film underneath.

- High puncture resistance
- · Heat welded installation

#### Typical use

- External
- · Balconies, terraces, roofs
- Base or mid layer in multi-layer systems

#### Substrates

Concrete

Gauge	2.5mm
Dimensions	15m x 1m (15m²)
Code	10525

ARDEX WPM 180 is an APP modified bitumen membrane, reinforced with fibreglass and polyester and protected by a heat-sensitive film on the underside.

- Combined polyester and fibreglass reinforcement
- Heat welded installation

#### Typical use

- External
- · Balconies, terraces, roofs
- Multi-layer membrane

#### Substrates

Concrete

Gauge	3.5mm
Dimensions	10m x 1m (10m²)
Code	10528

## ARDEX WPM 189

MINERAL-COATED TOP LAYER BITUMEN MEMBRANE



## ARDEX WPM 189+

CERAMIC-COATED TOP LAYER BITUMEN MEMBRANE



ARDEX WPM 189 is a dual-layer modified bitumen membrane, comprised of an SBS bottom layer for cold flexibility and APP (Atactic polypropylene) top layer for UV resistance.

- Excellent cold flexibility and elasticity
- Excellent resistance to atmospheric agents
- High puncture resistance

#### Typical use

- External
- Balconies, terraces, roofs
- As a cap sheet over base layers

#### **Substrates**

Base layers

Gauge	4mm
Dimensions	10m x 1m (10m <sup>2</sup> )
Codes	Black: 11324 Grey: 11242

ARDEX WPM 189+ is a 5mm dual-layer modified bitumen membrane, comprised of an SBS (styrene-butadiene-styrene) bottom layer for cold flexibility and APP top layer for UV resistance.

- · Excellent cold flexibility and elasticity
- Excellent resistance to atmospheric agents
- Ceramic chip for longevity and colour fastness

#### Typical use

- External
- · Balconies, terraces, roofs
- As a cap sheet over base layers

#### Substrates

· Base layers

Gauge	5mm
Dimensions	8m x 1m (8m <sup>2</sup> )
Codes	Grey: 32325 Black Gloss: 32326

P50 ARDEX Group ardex.co.nz P51

## ARDEX WPM 240



SOLVENT-BASED BITUMEN PRIMER

ARDEX WPM 240 is a solvent-based primer used to seal and prepare substrates prior to installing ARDEX bituminous membranes.

- Solvent-based
- For use with ARDEX bitumen systems
- Fast drying

Coverage	5m² per litre
Codes	20L Black: 10534 20L Clear: 30626

## ARDEX WPM 247



WATER-BASED BITUMEN PRIMER

ARDEX WPM 247 is a water-based primer used to seal and prepare substrates prior to installing ARDEX bituminous membranes.

- Water-based
- For use with ARDEX bitumen systems
- High coverage

Colour	Black
Coverage	6m² per litre
Codes	20L: 11171





ARDEX Bituminous Sealant is a one-component sealant with bitumen-based solvents, used for gluing, sealing and repairing bituminous membranes.

- Good primerless adhesion
- Easy to use
- UV stable

#### Typical use


- External
- Roofing
- Sealing membrane edges
- Between old bitumen membranes

#### Substrates

- Tin
- Aluminium
- Copper
- Brass
- Ceramic
- Bitumen
- Concrete
- Plaster
- Roof tiles

Colour	Black
Size	300ml
Code	25432

P52 ARDEX Group ardex.co.nz P53



### **ARDEX WPM 3000X**

**SELF-ADHESIVE BITUMINOUS MEMBRANE** 



## **ARDEX WPM 5000HD**

INDUSTRIAL-STRENGTH, **SELF-ADHESIVE BITUMINOUS MEMBRANE** 



ARDEX WPM 3000X is a peel-and-stick, SBS rubber modified bituminous membrane with a polyetheline film top-coating for damp-proofing underground structures.

- Cold application
- · Self-seals on contact with substrate
- · Radon and methane barrier

#### Typical use

- Below-ground applications
- Foundations
- Retaining walls
- Balconies
- Planter boxes
- · Decks under cement screeds

#### Substrates

- Concrete render and screeds
- · Fibre cement sheets
- · Structural or marine plywood
- Polystyrene blocks

Gauge	1.5mm
Dimensions	20m x 1m (20m²)
Code	10543

ARDEX WPM 5000HD is an industrial-strength, self-adhesive bituminous membrane, reinforced with polypropelene mesh.

- High mechanical characteristics
- · Radon and methane gas barrier
- Self-healing

#### Typical use

- · Below-ground applications
- Underground structures
- Trafficable structures covered with asphalt
- Expansion joints
- Underneath clay tiles or asphalt shingles

#### Substrates

- Concrete render and screeds
- · Fibre cement sheets
- Structural or marine plywood
- Polystyrene blocks

Gauge	1.5mm
Dimensions	20m x 1m (20m²)
Code	10544

## ARDEX DRS 10 GC



DRAINAGE PROTECTION MEMBRANE

ARDEX DRS 10 GC is a cuspated HDPE sheet with a geotextile layer that provides effective drainage and protection against backfill.

- Effective drainage of sub-surface water
- Excellent compressive strength
- 100% recycled material

#### Typical use

- Below-grade applications
- Basement foundations
- Retaining walls
- Planter boxes
- Bridge abutments
- Green roofs

Thickness	10mm
Dimensions	20m x 2m (40m²)
Code	32142

### ARDEX BITUMINOUS SEALANT



ARDEX Bituminous Sealant is a one-component sealant with bitumen-based solvents, used for gluing, sealing and repairing bituminous membranes.

- Good primerless adhesion
- Easy to use
- UV stable

#### Typical use

- External
- Roofing
- Sealing membrane edges
- Between old bitumen membranes

#### Substrates

- Tin
- Aluminium
- Copper
- Brass
- Ceramic
- Bitumen
- Concrete
- Plaster
- Roof tiles

Colour	Black
Size	300ml
Code	25432





SOLVENT-BASED BITUMEN PRIMER


ARDEX WPM 240 is a solvent-based primer used to seal and prepare substrates prior to installing ARDEX bituminous membranes.

- Solvent-based
- For use with ARDEX bitumen systems
- Fast drying

Coverage	5m <sup>2</sup> per litre dependent on substrate
Codes	20L Black: 10534 20L Clear: 30626








- Water-based
- For use with ARDEX bitumen systems
- High coverage

Colour	Black
Coverage	6m² per litre
Codes	20L: 11171

P56 ARDEX Group ardex.co.nz P57



## **ARDEX WPM 179**



LIOUID RUBBER **WATERPROOFING MEMBRANE** 



**ARDEX** 



ARDEX WPM 179 is a one-component, latex modified, bituminous elastomeric liquid waterproofing membrane used for patching or repairs.

- Quick drying
- · Contains root inhibitors
- Excellent chemical resistance

#### Typical use

- Below-grade
- Tanking

#### Substrates

- Masonty
- Concrete
- Steel
- · Sand cement screeds
- Renders

#### Colours

Black

#### Coverage

As a patch repair membrane: approx. 15m<sup>2</sup> As a waterproofing membrane: 8m<sup>2</sup>

Code 15L: 12981

ARDEX WPM 195 is a high-performance SBS modified bituminous membrane with added elastoplastomeric polymers.

- Excellent cold flexibility
- Strong adhesive strength
- · Positive vapour barrier

#### Typical use

- Below-grade
- Tanking

#### Substrates

• Concrete

Gauge 4mm

Dimensions 8m x 1m (8m<sup>2</sup>)

Code 25075

### ARDEX WPM 196

## MINERAL-COATED BITUMINOUS TANKING MEMBRANE



ARDEX WPM 196 is a SBS modified bituminous membrane, with excellent strength and dimensional stability.

- Positive vapour barrier
- Proven performance in cold regions
- Accommodates structural movements

#### Typical use

- Below-grade
- Tanking

Gauge	4mm
Dimensions	8m x 1m (8m <sup>2</sup> )
Code	26034

# ARDEX WPM 1000 RR

**WELDTEC™ ROOT REPELL** 



ARDEX WPM 1000 RR is a high-performance, heat-weldable membrane designed for areas exposed to soil and plants.

- Contains a premium root inhibitor
- WeldTec<sup>™</sup> technology for strong laps and detailing
- Excellent chemical resistance properties

#### Typical use

- · Green roofs
- · Retaining walls
- Planter boxes
- Anywhere susceptible to roots causing damage

#### **Substrates**

- Concrete
- Plywood
- Modified bitumen
- Malthoid
- ARDEX Polyiso or HD Cover Board
- Orientated strandboard
- CFC sheet
- Timber
- · Galvanised metal
- 7incalume
- · Polyurethane foam

Gauge	1mm
Dimensions	20m x 1.4m (28m²)
Code	24578



WELDTEC™ TANKING MEMBRANE



## ARDEX DRS 10 GC



DRAINAGE PROTECTION MEMBRANE

ARDEX WPM 1500 is a pre-applied, fleece-lined, weldable waterproofing membrane for below ground tanking and gas barrier applications.

- WeldTec<sup>™</sup> technology for strong laps and detailing
- Natural gas barrier
- · High elongation

#### Typical use

- · Below-grade
- Tanking
- Outside building sub-structures

#### **Substrates**

- Concrete
- Plywood
- Modified bitumen
- Malthoid
- ARDEX Polyiso or HD Cover Board
- · Orientated strandboard
- CFC sheet
- Timber
- Galvanised metal
- Zincalume
- · Polyurethane foam
- · Shot crete

Gauge	1.5mm
Dimensions	20m x 1.4m (28m²)
Code	19807

ARDEX DRS 10 GC is a cuspated HDPE sheet with a geotextile layer that provides effective drainage and protection against backfill.


- Effective drainage of sub-surface water
- Excellent compressive strength
- 100% recycled material

#### Typical use

- Below-grade applications
- · Basement foundations
- Retaining walls
- Planter boxes
- · Bridge abutments

Thickness	10mm
Dimensions	20m x 2m (40m <sup>2</sup> )
Code	32142

P60 ARDEX Group ardex.co.nz P61



ARDEX WPM 1955 is a hydrophilic, swelling, polymeric rubber joint for use in areas of fresh, brakish, saline or briny salt water.

- Solves construction detailing problems
- Unaffected by long-term wet-dry cycles
- Designed specifically for all environments


#### Typical use


- Salt water and fresh water
- Marine applications

#### Substrates

Concrete

Gauge	10mm
Dimensions	8m x 20mm
Code	30146







**WELDTEC™ INTERNAL UNDERTILE WATERPROOFING MEMBRANE** 





**WELDTEC™ EXTERNAL UNDERTILE WATERPROOFING MEMBRANE** 



ARDEX WPM 750 is a fleece-lined waterproofing sheet membrane specially formulated for the direct adhesion of internal tiled surfaces.

- WeldTec<sup>™</sup> technology for strong laps and detailing
- Fleece-lined for better adhesion
- Excellent flexibility

#### Typical use

- Internal
- Undertile

#### Substrates

- Concrete
- Plywood
- CFC sheet
- Timber
- Polyurethane foam
- Plasterboard

Gauge	0.75mm
Dimensions	20m x 1.4m (28m²)
Code	13319

ARDEX WPM 1000 is a fleece-lined waterproofing sheet membrane designed to be used on direct adhesion of tiled systems externally or for other non-exposed use.

- WeldTec<sup>™</sup> technology for strong laps and detailing
- Fleece-lined for better adhesion
- · Excellent flexibility

#### Typical use

- External
- Undertile

#### Substrates

- Concrete
- Plywood
- CFC sheet
- Timber
- · Polyurethane foam
- Plasterboard

Gauge	1.2mm
Dimensions	20m x 1.4m (28m²)
Code	16475

### ARDEX WA 98 A



NEW ZEALAND MADE ®

## WATERPROOFING MEMBRANE ADHESIVE



ARDEX WA 98 A is a high-performance membrane contact adhesive.

- Contact adhesive
- Solvent-based
- Ideal for bonding large areas

#### Typical use

- Horizontal or vertical
- Adhering ARDEX WeldTec<sup>™</sup> and butynol sheet membranes externally

#### Suitable membrane types

- WeldTec<sup>™</sup>
- Butynol

Working time	15 – 60 minutes
Coverage	4 – 8m² bond area per litre
Codes	20L: 13052 4L: 10870
	1L: 10869

ARDEX WeldTec™ Detailing Products ensure secure waterproofing in corners and edges of ARDEX WeldTec™ undertile membranes.

- Edge detailing
- Corner detailing
- Detail tape
- Weldtec Transition strip

#### Typical use

- Internal
- Undertile

#### Substrates


Various ARDEX Weltec membranes

#### Dimensions

Refer to ardex.co.nz for dimensions, quantities, and colours of each product



UNDERTILE DRAINAGE MAT



- Isolates tiles surface from substrate movement
- Allows passive drainage through surface
- Reduces likelihood of efflorescence

#### Typical use

- External
- Under tiling

#### Substrates

- Concrete
- Screed
- Plywood

•	CFC	sheet

Thickness	9mm
Dimensions	1.96m x 1.02m (2m <sup>2)</sup>
Code	30322





ARDEX UD 158 is a mesh tape used for the reinforcement of butted joins and seams in ARDEX drainage systems such as ARDEX UD 150.

- · Reduces likelihood of efflorescence
- Reinforcement for ARDEX UD 150
- Alkali-resistant mesh tape

#### Typical use

- External
- Under tiling
- Use with ARDEX UD 150

Dimensions	100mm x 25m
Code	39958

P66 ARDEX Group ardex.co.nz P67



### **ARDEX WPM 001**





TWO-PART UNDERTILE WATERPROOFING MEMBRANE



ARDEX WPM 001 is a tough, ready to use waterproofing membrane specifically designed for use under tiles. It has been uniquely formulated with synthetic microfibres to increase its strength and eliminate the need for a separate reinforcement mat.

• Single component undertile waterproofing membrane

**ONE-COMPONENT UNDERTILE** 

**WATERPROOFING MEMBRANE** 

- Fast drying one part acrylic membrane
- · Fibre reinforced

#### Location

· Internal wet areas, balconies and other areas that will be tiled or protected from regular foot traffic

#### **Substrates**

Code

- · Concrete, renders and screeds
- Wet area compatible fibre-cement sheet, plywood and plasterboard

**Drying times** Recoat time: 1-2 hrs Ready to tile: 48 hrs Full cure: 3 days Floors: 7.5m2 (2 coats) D.F.T. -Coverage 1.0mm Walls: 15m2 (2 coats) D.F.T. -0.5mm

10593

ARDEX WPM 002 is a durable, fast drying two component waterproofing membrane specifically designed for external undertile waterproofing.

- · Fibre reinforced for increased strength
- · Resistant to re-emulsification
- Extremely fast drying

#### Typical use

- Internal or external
- · Horizontal or vertical
- Undertile

#### **Substrates**

- Concrete
- · Renders and screeds
- · Fibre cement board
- Plasterboard (internal only)
- Plywood (internal only)

**Cure time** 3 days at 23°C Floors: 16m<sup>2</sup> Coverage Walls: 24m<sup>2</sup> Part A - Liquid - 20kg: 10595 Codes Part B - Powder - 20kg: 10597

### ARDEX WPM 155 RAPID



FAST-DRYING POLYURETHANE UNDERTILE MEMBRANE



ARDEX WPM 155 Rapid is a water-based, polyurethane-acrylic waterproofing membrane for high-performance under-tile waterproofing.

- Extended coverage
- Extremely fast drying
- Solvent-free

#### Typical use

- · Commercial or residential
- Internal or external

#### Substrates

- Concrete
- · Renders and screeds
- · Fibre cement board
- Plywood (internal only)
- Plasterboard
- CFC sheet

Cure time	Renders and screeds: 7 days Concrete: 28 days
Coverage	Refer to data sheet for applicable system
Codes	4L: 19728 15L: 19727

## ARDEX WPM 300



WATER-BASED EPOXY MEMBRANE

ARDEX WPM 300 is a two-component, epoxy polyamide membrane/barrier coating, which prevents rising damp and efflorescence.

- Adheres to damp surfaces and green concrete
- Approved for use with potable water
- Withstands hydrostatic pressure

#### Typical use

- Internal or external
- Walls or floors

#### **Substrates**

- Brick
- Masonry
- Concrete block
- Concrete
- Stone

Cure time	7 days
Coverage	1.5m <sup>2</sup> per litre
Codes	20L kit: 8000021 4L kit: 10207

## ARDEX DECKWEB

WOVEN POLYESTER
REINFORCEMENT CLOTH

ARDEX Deckweb is a reinforced cloth for use with liquid waterproofing membranes to build membrane thickness in critical areas such as cracks, movement joints and corners.

#### Typical use

Internal or external

Dimensions	50m x 190mm
Code	10293

### ARDEX ST TAPE



ARDEX ST Tapes are uncured, self-adhesive tapes used to reinforce critical areas and detailing when using ARDEX WPM 155 Rapid.

- High tear resistance
- Alkali resistance
- High elasticity

#### Typical use

Internal

Codes

• In conjunction with ARDEX WPM 155 Rapid

**Dimensions** STA Sheets: 2.4m x 400mm STB Tapes: 15m x 75mm

STA Sheets: 19216 STB Tapes: 16870

P70 ARDEX Group ardex.co.nz P71

## **ARDEX MULTIPRIME**



**WATER-BASED PRIMER** 



**SINGLE-PART** 



**PRIMER** 

ARDEX Multiprime is a water-based primer for improving adhesion of ARDEX products to various porous substrates.

- Quick drying
- Solvent-free
- Low VOC

#### Typical use

- Internal or external
- Walls and floors

#### Substrates

- · Fibre cement sheet
- Plasterboard
- Concrete renders and screeds
- Masonry
- Concrete blocks
- Aerated concrete

Drying time	15 – 30 minutes
Coverage	6m² per litre
Codes	20L: 10155 4J: 10156

ARDEX P 9 Single Part Primer is a water-based primer used for improving the adhesion of ARDEX products to smooth, dense and various non-porous substrates.

- Solvent-free
- Low VOC content
- Easy to apply


#### Typical use

- Internal or external
- · Walls and floors

#### Substrates

- · Internal particleboard
- Plywood
- Sheet timber
- Fibre-cement sheet
- Plasterboard
- Concrete renders and screeds
- Masonry
- Aerated concrete
- Concrete blocks
- Glazed tiles

Drying time	20 minutes
Coverage	6 – 10m² per litre
Code	4L: 16778





## **ARDEX POLYISO INSULATION BOARD**

PIR FOAM INSULATION BOARD

The ARDEX Polyiso Insulation Board is lightweight and provides high-energy efficiency through outstanding thermal resistance.

- Excellent dimensional and compressive strength
- Easy to handle
- Does not deplete earth's ozone layer

#### Typical use

- External
- Roofing
- Under ARDEX waterproofing membranes

Thickness	20mm - 140mm Contact ARDEX for availability of thichness
Coverage	2.4m x 1.2m
R-Values	R0.97 to R6.82 Check ardex.co.nz for more information

- System drawings are available for any ARDEX membrane
- We have designed details with a vapour barrier
- Contact specifications@ardexnz.com for help with wind uplift calculations

## **ARDEX HD COVER BOARD**

**HIGH-DENSITY POLYISO COVER BOARD** 

ARDEX HD Cover Board is a high density, closed-cell, Polyisocyanurate foam core for use as an insulative cover board.

- Outstanding thermal performance
- Only 5kg per board
- Easy to cut and handle

#### Typical use

- External
- Roofing
- Under ARDEX waterproofing membranes

Gauge	12.7mm
Coverage	2.25m x 1.22m
Code	12926



#### FOR FASTENING OF ARDEX **POLYISO BOARD**

ARDEX Polyiso Insulation Plates are specifically designed for attaching insulation and cover boards to roofing substrates. These plates provide a flat and smooth finishing as a result of the recessed head in the centre of the fastener plate, which limits any risk of puncturing a waterproofing membrane from beneath. To be used with ARDEX Fasteners.

#### Typical use

- External roofing
- With ARDEX thermal insulation systems
- Mechanically fastened systems

Code 24071

## **ARDEX FASTENERS**

#### **TPO AND INSULATION FASTENING**

ARDEX Fasteners are available as Heavy Duty Fasteners. They are specifically designed for mechanical attachment of ARDEX roofing insulation. To be used with Insulation Plates.

• 1000 pieces per pail

#### Typical use

- External roofing
- With ARDEX thermal insulation systems
- Mechanically fastened systems


#### Thread size

• 6.7mm

#### Screw length


• Varies 32mm to 356mm





## **ARDEX UD 150**





- Isolates tiles surface from substrate movement
- · Allows passive drainage through surface
- Reduces likelihood of efflorescence

#### Typical use

- External
- Under tiling

#### Substrates

- Concrete
- Screed
- Plywood
- CFC sheet
- ARDEX single-layer sheet membranes

Thickness	9mm
Dimensions	1.96m x 1.02m (2m²)
Code	30322

## **ARDEX DRS 10 GC**



#### DRAINAGE PROTECTION **MEMBRANE**

ARDEX DRS 10 GC is a cuspated HDPE sheet with a geotextile layer that provides effective drainage and protection against backfill.

- Effective drainage of sub-surface water
- Excellent compressible strength
- 100% recycled material

#### Typical use

- Below-grade applications
- Basement foundations
- Retaining walls
- Planter boxes
- Bridge abutments

Thickness	10mm
Dimensions	20m x 2m (40m²)
Code	32142




ARDEX UD 158 is a mesh tape used for the reinforcement of butted joins and seams in ARDEX drainage systems such as ARDEX UD 150.


- Reduces likelihood of efflorescence
- Reinforcement for ARDEX UD 150
- Alkali-resistant mesh tape

#### Typical use

- External
- Under tiling
- Use with ARDEX UD 150

Dimensions	100mm x 25m		
Code	39958		





#### DISCLAIMER

The technical details, recommendations and other information contained in this catalogue are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly, and in accordance with any applicable New Zealand Standard. Our instructions and recommendations are only for the uses they are intended.

We also reserve the right to update information without prior notice to you reflecting our ongoing research and development programme. Country specific recommendations (depending on local standards), Codes of Practice, Building Regulations or Industry Guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. ARDEX reserves the right to change packaging and weight of products at any time without notice due to production requirements.

© ARDEX New Zealand Ltd 2023 . All aforementioned products are the trade marks of ARDEX New Zealand Ltd, its licensors

NOTES		
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	

NOTES		
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	

