



---

# ARDEX Bituminous Roof Sealant

**One-Component, Bitumen-Based Sealant**

---

Easy to use

UV-Stable

Good primerless adhesion - Adheres well to many substrates

---

**ARDEX Australia Pty Ltd**  
20 Powers Road  
Seven Hills NSW 2147  
1300 788 780  
technicalservices@ardexaustralia.com  
www.ardexaustralia.com

**ARDEX New Zealand Ltd**  
32 Lane Street  
Woolston, Christchurch 8023  
0800 227 339  
info@ardexnz.com  
www.ardex.co.nz

# ARDEX Bituminous Roof Sealant

## One-Component, Bitumen-Based Sealant

---

### DESCRIPTION

ARDEX Bituminous Roof Sealant is a one-component, easy-to-use, UV-stable sealant with bitumen-based solvents. It is used for gluing and sealing on roofs. It is ideal for fast repairs of cracks, holes and fractures on roofs and between old bitumen membranes and can be applied over a multitude of surfaces including tin, aluminum, copper, brass, ceramic, bitumen, concrete, plasters, roof tiles and plaster tiles without the use of a primer.

### SUBSTRATE PREPARATION

The surface being adhered to must be clean, firm and free of dust, dirt, oil, grease, and other barrier materials. If there are any signs of contamination visible on the old membrane, they have to be thoroughly removed and the sealant has to be applied onto a sound surface. Alcohol and nitro-cleaners can be used for cleaning.

### INSTRUCTIONS

The sealant can be applied with a standard caulking gun. Alcohol and nitro-cleaners can be used for cleaning.

NOTE: Not suitable for gluing polyurethane and polystyrene.

### SKIN FORMATION TIME

5 – 15 minutes depending on ambient and substrate temperature.

### PACKAGING

ARDEX Bituminous Roof Sealant is in a 300ml cartridge.

### SHELF LIFE

24 months when stored in a dry place in the original, unopened packaging.

### SAFETY DATA

Flammable liquid and vapour. Harmful to aquatic life with long lasting effects. Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. In case of contact with the eyes rinse with running water (15mins)

including removal of contaminated clothing. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust/ fume/ gas/ mist/ vapours/ spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet SDS at [www.ardexaustralia.com](http://www.ardexaustralia.com)

---

INTENTIONALLY LEFT BLANK



## TECHNICAL DATA

### UNCURED SEALANT

<b>Chemical basis</b>	Bitumen with solvents
<b>Form</b>	Thick black paste
<b>Curing mechanism</b>	Solvent evaporation
<b>Specific gravity</b>	1440 ± 30 kg/m <sup>3</sup>
<b>Dry material content</b>	89 – 94 %
<b>Inflammation point in closed container</b>	>30 °C
<b>Skin formation time</b>	5 – 15 minutes
<b>Application temperature</b>	+5°C to +35°C

### CURED SEALANT

<b>Consistency</b>	Plastic
<b>Temperature resistance</b>	-30°C to +80°C
<b>Hardness Shore A</b>	10 – 15

#### **ARDEX Australia Pty Ltd**

Phone: 1300 788 780  
Fax: 1300 780 102

#### **Toll Free Technical Services:**

1800 224 070 (Australia)

#### **ARDEX New Zealand Ltd**

Phone: 0800 227 339  
Fax: (03) 3849779

February 2017

#### **DISCLAIMER**

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations are only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice building regulations or industry guidelines may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

© ARDEX Australia Pty Ltd 2017.

All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.