



ARDEX WPM 657

TPO General Purpose Sealant

Excellent resistance to ozone, ultraviolet and general weathering

Excellent resistance to heat, cold and water

Excellent adhesion to ARDEX TPO sheet membranes

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX WPM 657

TPO General Purpose Sealant

DESCRIPTION

ARDEX WPM 657 TPO General Purpose Sealant is a high quality sealant with excellent adhesion to a variety of surfaces, and for use in conjunction with ARDEX TPO Systems as a Termination Bar Caulk, and TPO Cut Edge/Seam Edge treatment, where required by ARDEX details.

CHARACTERISTICS

- Excellent resistance to ozone, ultraviolet and general weathering
- Excellent resistance to heat, cold and water.
- Excellent adhesion to ARDEX TPO sheet

Technical

Base	EPDM Rubber
Colour	White
Solids	80% (nominal)
Specific Gravity	1.40 – 1.46
V.O.C. content	Less than 250 g/l

PREPARATION

Surfaces to receive ARDEX WPM 657 TPO General Purpose Sealant must be clean, dry, sound, frost free, and grease free. When cleaning substrates to receive ARDEX WPM 657 TPO General Purpose Sealant, detergent or soap and water treatments are not recommended. Solvent cleanings are recommended to clean protective films, oils, etc.

APPLICATION

ARDEX WPM 657 TPO General Purpose Sealant is designed to be applied with an ordinary caulking gun. Cut nozzle to desired bead size and apply sealant, making sure that the sealant is in good contact with all sides of the joint. Tooling of ARDEX WPM 657 General Purpose Sealant is not required.

COVERAGE

For continuous bead of 6 mm x 6 mm: 183 m per carton.

* Estimated coverage rates.

PACKAGING/STORAGE/SHELF LIFE

Packaging:	25 cartridges per carton.
Storage:	Store in original sealed container at temperatures between 15° C and 25° C.
Shelf Life:	12 months, when stored in above –mentioned conditions. Shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONS

Refer to Material Safety Data Sheet.

Wear eye protection. Use only in well ventilated areas. Do not contaminate with foreign materials. For professional use only. Keep out of reach of children. Thinning is not allowed. Recommended cleaner is xylene or acetone before sealant cures. After sealant is cured, it can be removed by abrasion or mechanical means. Wear protective gloves when using.

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program.

Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations.

The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

ARDEX Australia Pty Ltd

New South Wales	Ph (02) 9851 9100	Fax (02) 9838 7970
Queensland	Ph (07) 3817 6000	Fax (07) 3881 3188
Victoria/Tasmania	Ph (03) 9308 9255	Fax (03) 9308 9332
South Australia	Ph (08) 8268 2511	Fax (08) 8345 3207
Western Australia	Ph (08) 9256 8600	Fax (08) 9455 1227

ARDEX New Zealand Ltd

Auckland	Ph (09) 5800 005	Fax (09) 5799 963
Wellington	Ph (04) 5685 949	Fax (04) 5686 376
Christchurch	Ph (03) 3843 029	Fax (03) 3849 779

Technical Services Toll Free: 1800 224 070