

ARDEX WPM 750

WELDTEC INTERNAL UNDERTILE SHEET MEMBRANE



ARDEX WPM 750 is a fleece-lined waterproofing sheet membrane specially formulated for the direct adhesion of tiled surfaces. It uses heat-welded laps and seams to create a superior bond, consistent gauge and allow a quick installation. ARDEX WPM 750 has excellent flexibility, durability, and superior resistance to tearing, cracking, bubbling and absorption.

Benefits

- BRANZ Appraisal (No. 727)
- Manufactured in New Zealand
- Heat-welded laps and seams
- Fleece-lined for excellent adhesion
- Begin tiling after 60 minutes
- Thin and consistent membrane thickness
- Excellent flexibility - no requirement for fillet or bond breakers
- Excellent resistance to tearing and cracking

Use

As an internal waterproofing membrane for directly adhered tiling systems. Suitable for use with most ARDEX tile adhesives in domestic and commercial locations over most common substrates.

Location

Internal wet areas

Substrates

- Structural or marine plywood
- Concrete
- CFC sheet
- Timber
- Closed cell polyurethane
- Paper-faced plasterboard

Size

Roll of 1.4m x 20m x 0.75mm (28m²)

Packaging

Roll

Code

13319



BRANZ Appraised
Appraisal No.727 [2017]

To find out more
call 0800 227 339 or
visit www.ardex.co.nz



SYSTEMARDEX
PREMIUM PERFORMANCE

WeldTec™